SITE CONTROLLER | COMMANDER EF

Fit for purpose.

COMMANDER EF

Commander EF utilizes Verifone's fit for purpose Commander hardware and our state-of-the-art forecourt and electronic payments software to deliver a comprehensive solution that maximizes uptime. Commander EF delivers the fastest transaction times in the industry, even in the most complex environments, with multiple dispenser types, multiple loyalty programs, media, and mobile payments all running at once.

- Fastest transaction times for the most complex forecourt and payment environments
- Utilizes standards from IFSF and Conexxus for payment, forecourt control, loyalty and mobile payment,
- Easily connects to any POS enabling quick and seamless boarding of new loyalty and mobile payment providers.
- Built-for-purpose hardware for increased up time and reliability
- Vast network of certified payment, mobile payment, and loyalty partners across the industry



8GB DDR4 SoDIMM	Peripheral Ports	Expansion: 2 Hard Drive Slots
Intel® Pentium Gold G5400T Dual Core 3.1GHz CPU		Expansion: 2 Slots for Additional CPU Functionality Expansion: 3 PCIe Peripheral Card Slots
Secure real-time Linux	Physical	14.75" W × 6.25" H × 16" L
7-Segment Status LEDs Diagnostic Console Port Diagnostic Switches Heartbeat LED Power LED Soft Reset Button	Environmental	Operating Temperature: 0° to 40° C (32° to 104° F) Storage Temperature: -20° to 60° C (-4° to 140° F) Relative Humidity at 40° C (104° F): 15% to 95%,
Connectivity 1 × USB 3.1 Port 2 × 10/100/1000 Ethernet Ports 16 × RJ-45 RS-232 Serial Ports Scalable to 24 RS-232 Ports Ports		Non-condensing
	Storage	HDD or SSD, 120 GB or greater
	Optional Features	Communications: Software-controlled
Backup Battery		12V DTR Power
	Intel® Pentium Gold G5400T Dual Core 3.1GHz CPU Secure real-time Linux 7-Segment Status LEDs Diagnostic Console Port Diagnostic Switches Heartbeat LED Power LED Soft Reset Button 1 × USB 3.1 Port 2 × 10/100/1000 Ethernet Ports 16 × RJ-45 RS-232 Serial Ports Scalable to 24 RS-232 Ports	Intel® Pentium Gold G5400T Dual Core 3.1GHz CPUPhysicalSecure real-time LinuxPhysical7-Segment Status LEDs Diagnostic Console Port Diagnostic Switches Heartbeat LED Power LED Soft Reset ButtonEnvironmental1 × USB 3.1 Port 2 × 10/100/1000 Ethernet Ports 16 × RJ-45 RS-232 Serial Ports Scalable to 24 RS-232 PortsStorage Optional Features



Copyright 2023 VeriFone Systems, Inc. All rights reserved. Verifone logo are either trademarks or registered trademarks of Verifone in the United States and/or other countries. All other trademarks or brand names are the properties of their respective holders. All features and specifications are subject to change without notice, and do not constitute a warranty of any kind, including, but not limited to, warranties of merchantability or fitness for a particular purpose. Product display image for representation purposes only. Actual product display may vary. Reproduction or posting of this document without prior Verifone approval is prohibited.