COUNTERTOP | T650c

Commerce-building countertop solution.

T650c





The Verifone T650c offers turnkey integrated POS, payment services and reporting. With a large, vibrant display, customer-friendly screen rotation and front and forward-facing cameras, the T650c provides easy viewing and flexible payment options to engage customers and grow commerce in new and exciting ways.

- 5.5" Capacitive color multi-touch screen with screen rotation
- Full-motion video support with high-quality audio
- Verifone's proprietary Navigator solution for the visually impaired
- 5MP camera ideal for scanning and accepting alternative payment methods

- Fewer printer roll changes thanks to larger 50 mm paper roll
- Security where you need it with Verifone's locked down version of Android
- Utilizes the power of Verifone Cloud Services for further customization and to add revenue building streams like eCommerce, Pay-by-Link, Advanced Payment Methods and more.

Display	5.5" Color LCD Capacitive Multi-touch Screen LED Backlight Screen Rotation Resolution 720 x 1280 HD
Multimedia	Audio Jack Speaker Microphone Video & Audio Playback
User Interface	Touchscreen PIN Entry Verifone Navigator Volume Buttons
Camera Barcode Scanner	Barcode + OCR + QR Decode Front 0.3 MP Fixed Focus Rear 5 MP Auto Focus
Printer	50mm Paper Roll
Card Readers	Magstripe ISO 7810, 7811, 7813 Smart Card EMVCo Approved
Contactless	EMVCo Approved Supports Advanced Payment Methods Supports Major NFC/Contactless Schemes
Connectivity	2G + 3G + 4G CAT 4 Bluetooth® v4.2 Geolocation WiFi 2.4GHz + 5GHz 802.11 a/b/g/n

Memory	2GB RAM + 16GB Flash Micro SD
Operating System	Verifone Secure OS, AVOS Based on Android 8.1
Processor	ARM Cortex A7 Quad Core, 1.1 GHz
Security	PCI 5.x Approved
Connections	LAN 10/100 Base-T RS232 USB Type-A USB Type-C
Power	Adapter 9VDC, 2.5A Rating 9V, 2.5A, DC Jack
Physical	211mm L x 84mm W x 72mm H Weight: 456g
Environmental	Operating Temperature: -10° to 50° C (14° to 122° F) Storage Temperature: -20° to 70° C (-4° to 158° F) Relative Humidity: 10% to 90%, Noncondensing
Other Standard Features	Card Slots: 2 SAM Slots