



Verifone V200c

The Verifone V200c, part of the Verifone Engage portfolio, offers the latest in next-generation features, functionality and versatility. Packed with more speed, an interactive user interface and enhanced security, the V200c is the ideal choice for providing your customers with a unique experience at the point of sale. The V200c leverages the power of Verifone's new architecture, the latest Linux-based operating system and a modern application environment to deliver everything you need in a countertop device and more.

- Color LCD with sound capabilities to drive multimedia usage
- Modern, robust design—ideal for countertop use
- Faster processing to accommodate advanced multimedia usage
- Maximum security and compliance with end-to-end encryption
- Accepts all payment inputs including NFC/contactless, EMV chip and PIN, and magstripe
- Advanced commerce capabilities available, including BLE/beaconing support



Specifications

Processor

600 MHz, Cortex A9 32-bit RISC processor, 1500 MIPS; optional graphic accelerator

Memory

384 MB (256 MB Flash, 128 MB SDRAM); optional: 1024 MB (512 MB Flash, 512 MB SDRAM, microSD)

Display

2.8" QVGA, color LCD

Operating System

V/OS (Linux-based)

Connectivity

Dial-up, Ethernet; optional: 5GHz + 2.4GHz WiFi, Bluetooth 4.2

Printer

30 lps, 40 mm paper roll

Card Readers

Triple track MSR: ISO 7810, 7811, 7813; smart card reader: EMVCo-approved

Contactless

ISO14443 A&B, MiFare, ISO18092-capable, EMVCo L1 certification, supports major NFC/contactless schemes

Peripheral Ports

2 USB connectors: 1 host, 1 host/client; 1 RS-232-powered

Audio

Buzzer; optional mono audio

Security

PCI PTS 4.X-approved

Power

AC input 100-240VAC, 50/60Hz; DC output 11.6V 1.55A

Environmental

Operating temperature: 0° to 50° C (32° to 122° F); storage temperature: -20° to 60° C (-4° to 140° F); relative humidity: 5% to 90%, non-condensing

Physical

190 mm L x 80 mm W x 70 mm H; 381g weight

Other Standard Features

2 SAM slots, backlit keypad