Verifone®

Commander Site Controller

Commander Site Controller from Verifone offers convenience store owners a versatile site management solution providing increased speed in payment acceptance, fueling operations, and back-office store control. Commander is certified across all dispenser types, payment networks, and oil brands. The solution features Commander Console, a cloud-based software that allows owners to manage all aspects of their business, from fuel to payment and store operations, quickly and easily from any web-enabled device.

The Commander system architecture includes expansion slots and ports to add capacity as your business grows. This ensures fuel functionality and superior performance for years to come. Commander is designed specifically for the convenience retail industry, and is purpose-built for years of trouble-free service.

Commander Dashboard
Verifone Commander Dashboard gives c-store owners tremendous flexibility in supporting their businesses, with real-time access to multi-site sales data through an easy-to-use dashboard. The software is available on iOS and Windows, allowing managers and business owners to access a valuable set of operational matrices that are graphical and easy to navigate; sales data can be filtered by location, site, product type, and more. In addition, managers can create organization hierarchies, groups, user accounts, and permissions for ultimate security and control. Experience up-to-the- minute business updates with this remote management tool.

Specifications

Site Controller

Memory
4GB DDR2 SDRAM, scalable to 8GB

Diagnostic Panel
Soft reset button, diagnostic console port, 7-segment status LEDs, heartbeat LED, power LED, diagnostic switches

Storage
8GB solid state mass storage plus 160GB hard drive scalable to 1TB hard drive

Connectivity
1 × USB 2.0 ports; 2 × 10/100/1000 Ethernet ports; 16 × RS-232 serial ports, scalable to 24 ports

Processor
2.10 GHz Intel Core i3-2310E CPU, scalable to Intel Core i7

Communications
8 RJ-45, RS-232 serial ports with optional software-controlled 12V DTR power; Diagnostic Panel for fast debugging

Operating System
Secure real-time Linux, backup battery for power loss protection

Expansion Capability
2 slots for additional CPU functionality, 3 PCIe peripheral card slots, 2 hard drive slots

Environmental
0º C to 40º C operating temperature, -20º C to 60º C, 15% to 95% relative humidity at 40o C

Physical
14.75" W × 6.25" H × 16" L

Commander Dashboard

Minimum System Requirements
Commander Site Controller Base 38, broadband connection

Browser
Supports Internet Explorer 10 and higher, Mozilla Firefox 4.0 and higher, Google Chrome, Safari

Mobile Device
Supports mobile devices with screens 7.5" and larger

Operating Systems
Windows and iOS