

# V240m



The V240m, part of the Verifone Engage portfolio, combines the latest in features, functionality, and performance into one efficient and cost-effective solution. Boasting a large, 3.5" color touch display, more memory, faster processor and multiple connectivity options, this full-function portable payment device makes doing business on the go easy. Whether merchants are looking to accept basic payment transactions or explore more advanced capabilities like paying with points, digital couponing, and other value-added services, the V240m makes it possible. Ideal for pay-at-the-table, curbside delivery, kiosks and line-busting.

- New, intuitive user interface makes it easy to navigate
- Large 3.5" capacitive touchscreen and stunning HVGA resolution
- EMV-ready and fully compliant with the latest PCI 5.X requirements
- Accepts all payment types: NFC/contactless, mobile wallets, EMV, magstripe
- Utilizes the power of Verifone Cloud Services for point-of-sale customization, device management, security, and support

## Specifications

### Processor

MHz, Cortex A9 32-bit RISC processor, 1500 MIPS

### Memory

1024 MB (512 MB Flash, 512 MB SDRAM), microSD

### Display

3.5" HVGA capacitive touch screen, Corning® Gorilla® Glass 3 technology

### Operating System

V/OS (Linux-based)

### Connectivity

Standard options: 4G 5 GHz + 2.4 GHz Wi-Fi; Bluetooth® 4.2 low energy or 3G + Bluetooth 4.2 low energy + 2.4 GHz Wi-Fi

### Printer

30 lps, 40 mm paper roll

### Audio

Speaker

### Card Readers

Triple track MSR: ISO 7810, 7811, 7813; smart card reader: EMVCo-approved

### Contactless

ISO 14443 Types A and B, ISO 18092- capable, EMVCo L1 certification, MIFARE, supports major NFC/CTLS schemes

### Peripheral Ports

Single USB connector for 1 host/client, separate charging connector

### Security

PCI PTS 5.X-approved

### Power

Battery: 3.7 V/2450 mA Li-ion; PSU: 100- 240 VAC w/ output DC 5 V, 1 amp

### Physical

162.9 mm L × 75.3 mm W × 53.4 mm H

### Environmental

Operating temperature: 0° to 50° C (32° to 122° F); storage temperature: -20° to 60° C (-4° to 140° F); relative humidity: 5% to 90%, non-condensing

### Other Standard Features

2 SAM slots, geolocation, backlit keypad, dual SIM

### Options/Accessories

Charge-only base  
Full-featured base: powered RS-232, dial-up, Ethernet, USB client, USB host, Bluetooth  
Privacy shield